

Mrs Mpho Nembilwi Nkangala District P O Box 437 MIDDLEBERG 1050 By email_nembilwim@nkangaladm.gov.za' Date 07 September 2020

Enquiries E Madike Tel +27 13 647 9199

Dear Mrs Mpho Nembilwi

Ref Kendal Power Station AEL (17/4/AEL/MP312/11/15)

KENDAL POWER STATION'S EMISSIONS REPORT FOR THE MONTH OF JUNE 2020

This is a monthly report required in terms of Section 7.4 in the Kendal Power Station's Atmospheric Emission License. The emissions are for Eskom Kendal Power Station.

Note: This report was reviewed by Ebrahim Patel from Eskom Generation Division | Asset Management | Mechanical Engineering Centre of Excellence | Air Pollution Control

Compiled by:

Tshilidzi Vilane

ENVIRONMENTAL OFFICER-KENDAL

Date: 07/09/2020

Verified by:

SENIOR TECHNICIAN BOILER ENGINEERING- KENDAL

Date: 07/09/2020

KENDAL POWER STATION'S EMISSIONS REPORT FOR THE MONTH OF JUNE 2020

Validated by:

Tendanı Rasıvhetshele

Robinstslan 2

ACTING BOILER ENGINEERING MANAGER-KENDAL

Date 08/09/2020

Supported by:

Maliborigwe Mabizela

ACTING ENGINEERING MANAGER-KENDAL

Approved by

ACTING GENERAL MANAGER-KENDAL

Date 08/09/2020

14/09/2020


Date



JUNE 2020

ESKOM

KENDAL POWER STATION MONTHLY EMISSIONS REPORT
Atmospheric Emission License 17/4/AEL/MP312/11/15



1 RAW MATERIALS AND PRODUCTS

Raw Materials	Raw Material Type	Units	Consumption Rate Jun-2020
and	Coal Tons		909 009
Products	Fuel Oil	Tons	1663.11
	Deaduct / Du Deaduct		DEPT. CONT. TO SERVICE
	Product / By-Product	Units	Production Rate Jun-
Production	Name		2020
Production Rates	Name Energy	Units	
	Name		2020

2 ENERGY SOURCE CHARACTERISTICS

Coal Characteristic	Units	Stipulated Range	Monthly Average Content	
Sulphur Content	%	0.7 TO >1 (%)	0.770	
Ash Content	%	30 TO >40 (%)	30.640	

3 EMISSION LIMITS (mg/Nm³)

Associated Unit/Stack	РМ	SOx	NOx
Unit 1	100	3500	1100
Unit 2	100	3500	1100
Unit 3	100	3500	1100
Unit 4	100	3500	1100
Unit 5	100	3500	1100
Unit 6	100	3500	1100

4 ABATEMET TECHNOLOGY (%)

Associated Unit/Stack	Technology Type	Efficiency Jun-2020	Technology Type	Utlization Jun-2020
Unit 1	ESP + SO ₃	99.9%	so,	100.0%
Unit 2	ESP + SO,	99.8%	so,	98.8%
Unit 3	ESP + SO;	99.4%	SO,	62.7%
Unit 4	ESP + SO ₃	99.1%	SO,	96.0%
Unit 5	ESP + SO;	Unit off	so,	Unit off
Unit 6	ESP + SO ₃	98.8%	so,	Data not available (PI server frozen)

Note: ESP plant does not have bypass mode operation, hence plant 100% Utilised

5 MONITOR RELIABILITY (%)

Associated Unit/Stack	PM	SO ₂	NO	Oı
Unit 1	100.0	12.2	12.2	0.0
Unit 2	99.9	0.0	0.0	0.0
Unit 3	58.9	16.9	17.6	0.0
Unit 4	89.3	0.0	0.0	0.0
Unit 5	Unit off	Unit off	Unit off	Unit off
Unit 6	94.0	0.0	0.0	0.0

Unit 6 94.0 0.0 0.0 0.0 0.0 0.0 Note: Low gaseous monitor reliability is due to defective analysers as a result of unavailability of spares, Maintenance working on this issue.

6 EMISSION PERFORMANCE

Table 6.1 Monthly tonnages for the month of June 2020

Associated Unit/Stack	PM (tons)	SO ₂ (tons)	NO, (tons)
Unit 1	60 8	3 884	1 380
Unit 2	100 8	3 763	1 663
Unit 3	297 3	2 343	885
Unit 4	369 5	3 401	1 169
Unit 5	Unit off	Unit off	Unit off
Unt 6	414 9	5 992	2 482
SUN	1 243 23	19 383	7 579

Table 6.2 Operating days in compliance to PM AEL Limit - June 2020

Associated Unit/Stack	Normal	Grace	Section 30	Contraventi on	Total Exceedance	
Unit 1	29	0	0	0	0	32 6
Unit 2	24	3	0	0	3	65 9
Unit 3	0	2	0	20	22	215 6
Unit 4	1	- 2	0	19	21	290 5
Unit 5	Unit off	Unit off		Unit off	Unit off Unit off	
Unit 6	0		0	30	30	228 6
CHIL	6.4	-		69	76	

Table 6.3 Operating days in compliance to SOx AEL Limit - June 2020


Associated Unit/Stack	Normal	Grace		0 441	Total Exceedance	Average SOx (mg/Nm²)
Unit 1	30	0	0	0	0	1 925 3
Unit 2	28	n	0	0	0	2 458 1
Unit 3	24	0	0	0	0	1 635 4
Unit 4	22	n	0	o	0	2 661 2
Unit 5	- 22	0	0	0	0	
Unit 6	30	0	0	0	0	2 441 1
SUM				0	0	


Table 6.4: Operating days in compliance to NOx AEL Limit - June 2020

Associated Unit/Stack	Normal	Grace	Section 30	Contraventi on	Total Exceedance	Average NOx (mg/Nm³)
Unit 1	30	0	0	0	0	684.0
Unit 2	28	0	0	. 0	0	1 086.3
Unit 3	24	0	0	0	0	617.6
Unit 4	22	0	0	0	0	914.4
Unit 5	0	0	0	0	0	
Unit 6	30	0	0	0	0	1 011.4
SUM	134	0	0	0	0	


Table 6.5: Legend Description

Condition	Colour	Description	
Normal		Emissions below Emission Limit Value (ELV)	
Grace	8-1177	Emissions above the ELV during grace period	
Section 30	1000	Emissions above ELV during a NEMA S30 incident	
Contraventio		Emissions above ELV but outside grace or S30 incident conditions	







High PM emissions can be attributed to poor availability of Dust Handling Plant resulting to ash backlogs causing poor performance of the electrostatic precipitators fields.




Unit 3 high PM emissions can be attributed to poor availability of Dust Handling Plant resulting to ash backlogs causing poor performance of the electrostatic precipitators fields.




Unit 4 high PM emissions can be attributed to poor availability of Dust Handling Plant resulting to ash backlogs causing poor performance of the electrostatic precipitators fields.







Unit 6 high PM emissions can be attributed to poor availability of Dust Handling Plant resulting to ash backlogs causing poor performance of the electrostatic precipitators fields.




Note that gaseous emissions for unis 1 were manually entered using independant third party QAL2 parallel test reports due to defective CEMS monitors.




Note that gaseous emissions for unit 2 were manually entered using Independant third party QAL2 parallel test reports due to defective CEMS monitors.




Note that gaseous emissions for unit 3 were manually entered using Independant third party QAL2 parallel test reports due to defective CEMS monitors.




Note that gaseous emissions for unit 4 were manually entered using independant third party QAL2 parallel test reports due to defective CEMS monitors.







Note that gaseous emissions for unit 6 were manually entered using Independant third party QAL2 parallel test reports due to defective CEMS monitors.




Note that gaseous emissions for unit 1 were manually entered using Independant third party QAL2 parallel test reports due to defective CEMS monitors.




Note that gaseous emissions for unit 2 were manually entered using Independant third party QAL2 parallel test reports due to defective CEMS monitors.




Note that gaseous emissions for unit 3 were manually entered using Independant third party QAL2 parallel test reports due to defective CEMS monitors.



Note that gaseous emissions for unit 4 were manually entered using Independant third party QAL2 parallel test reports due to defective CEMS monitors.





Note that gaseous emissions for unit 6 were manually entered using Independant third party QAL2 parallel test reports due to defective CEMS monitors.

7 COMMENTS

Note that gaseous emissions for units 1,2,3, 4 & 6 were manually entered using Independant third party QAL2 parallel test reports due to defective CEMS monitors.

Unit 5 was still offload during the whole months of June 2020

Units 2,3,4 & 6 high PM emissions can be attributed to poor availability of Dust Handling Plant resulting to ash backlogs causing poor performance of the electrostatic precipitators fields.

Average SRM velocity values from the latest correlation report were used on the gaseous emissions on Unit 1, 2, 3 & 4 due to defective CEMS monitors and velocity correction factors were set M=1 and C=0 Average AMS velocity values from December 2019 correlation report were used for the gaseous emissions on unit 6 with the velocity correction factors

8 COMPLAINTS

There were no complaints for the months of June 2020