

Ms Nompumelelo Simelane Nkangala District Municipality PO Box 437 Middleburg 1050

Date:

April 2024

Enquiries: Lesiba Kgobe Tel: +27 13 699 7817

Ref: Kusile Power Station AEL (17/4/AEL/MP311/12/01)

Dear Ms. Simelane

KUSILE POWER STATION'S MONTHLY EMISSIONS REPORT FOR NOVEMBER 2023 REV 02

Resubmission of monthly emissions report for November 2023.

Hoping the above will meet your satisfaction.

Yours sincerely

Christopher Wani

ACTING GENERAL MANAGER DATE: 25 4/2024

1. KUSILE POWER STATION MONTHLY EMISSIONS REPORT: Atmospheric Emission License 17/4/AEL/MP311/12/01



2 Raw Materials and Products

Raw Materials and Products	Raw Material Type	Units	Max Permitted Consumption Rate	Consumption Rate Nov-2023
	Coal	Tons	1 818 083	682 115
	Fuel Oil	Tons	5 533	1534.862
	Limestone Tons 72 917		72 917	5538
	Product / By-Product Name	Units	Max Production Capacity Permitted	Indicative Production Rate Nov-2023
	Energy	GWh	3 321.216	1 296.081
Production Rates	Ash	Tons	663 583	204 634.500
-	Gypsum	Tons	129 250	3 101.280
	RE PM	kg/MWh	not specified	0.260
		kg/MWh		The second second

3 Energy source characteristics

Fuel Characteristic	Units	Stipulated Range	Monthly Average Content
Coal Sulphur	%	1.3	20.430
Ash in Coal	%	38	0.800
Fuel Oil Sulphur	%	3.5	2.540
Ash in FO	%	0.02	0.010

$KUSILE\ POWER\ STATION'S\ MONTHLY\ EMISSIONS\ REPORT\ FOR\ NOVEMBER\ 2023\ REV\ 02-17/4/AEL/MP311/12/01$

4 Emissions Limits (mg/Nm³)

Associated Unit/Stack	PM	SO ₂	NOx
East	50	3500	750
West	50	1000	750

5 Abatement Technology (%)

Associated Unit/Stack	Technology Type	Efficiency Nov- 2023	Utilisation Nov - 2023	Technology Type	Efficiency Nov-2023	Utilisation Nov- 2023
Unit 1	FFP	99.779%	100%	FGD	Out of service	Out of service
Unit 2	FFP	99.999%	100%	FGD	Out of service	Out of service
Unit 3	FFP	99.724%	100%	FGD	Out of service	Out of service
Unit 4	FFP	99.984%	100%	FGD	99.962%	100%

Note: Both the FFP and FGD does not have bypass mode operation, hence plant 100% Utilised.

6. Monitoring reliability (%)

Associated Unit/Stack	PM	SO ₂	NO
Unit 1	100.0	100.0	100.0
Unit 2	100.0	100.0	45.8
Unit 3	100.0	99.9	99.3
Unit 4	100.0	98.5	100.0

Unit 2 NOx monitor reliability was below 80% threshold due to faulty monitor.

7. Emissions Performance

Table 7.1: Monthly tonnages for the month of November - 2023

Associated Unit/Stack	PM	SO ₂	NO _x
Unit 1	138.4	3 952	1 107
Unit 2	0.0	78	18
Unit 3	190.9	3 717	1 005
Unit 4	7.7	101	834
SUM	337.1	7 849	2 964

KUSILE POWER STATION'S MONTHLY EMISSIONS REPORT FOR NOVEMBER 2023 REV 02 - 17/4/AEL/MP311/12/01

Table 7.2: Operating days in compliance to PM AEL Limit - November 2023

Associated Unit/Stack	Normal	Grace	Section 30	Contravention	Total Exceedance	Average PM (mg/Nm³)
Unit 1	10	8	0	12	20	55.6
Unit 2	2	.0	0	0	0	3.8
Unit 3	1	3	0	26	29	83.0
Unit 4	30	0	0	0	0	4.6
SUM	43	11	0	38	49	

Table 7.3: Operating days in compliance to SO₂ AEL Limit – November 2023


Associated Unit/Stack	Normal	Grace	Section 30	Contravention	Total Exceedance	Average SO ₂ (mg/Nm³)
Unit 1	30	0	0	0	0	1 499.4
Unit 2	3	0	0	0	0	1 371.3
Unit 3	30	0	0	0	0	1 567.4
Unit 4	30	0	0	0	0	57.9
SUM	93	0	0	0	0	


Table 7.4: Operating days in compliance to NOx AEL Limit -November 2023


Associated Unit/Stack	Normal	Grace	Section 30	Contravention	Total Exceedance	Average NOx (mg/Nm³)
Unit 1	30	0	0	0	0	417.2
Unit 2	3	0	0	0	0	324.1
Unit 3	30	0	0	0	0	428.6
Unit 4	30	0	0	0	0	477.2
SUM	93	0	0	0	0	


Table 7.5: Legend Description


Condition	Colour	Description			
Normal		Emissions below Emission Limit Value (ELV)			
Grace		Emissions above the ELV during grace period			
Section 30		Emissions above ELV during a NEMA S30 incident			
Contravention		Emissions above ELV but outside grace or S30 incident conditions			



















 $KUSILE\ POWER\ STATION'S\ MONTHLY\ EMISSIONS\ REPORT\ FOR\ NOVEMBER\ 2023\ REV\ 02-17/4/AEL/MP311/12/01$














8. Shut down and Light up information

Unit No. 1	Eve	nt 1	Event 2		
Breaker Open (BO)	3:30 am	2023/11/03	3:30 pm	2023/11/08	
Draught Group (DG) Shut Down (SD)	3:35 am	2023/11/03	DG did not trip or SD	DG did not trip or SD	
BO to DG SD (duration)	00:00:05	DD:HH:MM	n/a	DD:HH:MM	
Fires in time	3:50 am	2023/11/03			
Synch. to Grid (or BC)	10:35 am	2023/11/03			
Fires in to BC (duration)	00:06:45	DD:HH:MM		DD:HH:MM	
Emissions below limit from BC (end date)	not > limit	not > limit			
Emissions below limit from BC (duration)	n/a	DD:HH:MM		DD:HH:MM	

Unit No. 2	Eve	nt 1	Eve	nt 2
Breaker Open (BO)	BO previously	BO previously	1:05 am	2023/11/30
Draught Group (DG) Shut Down (SD)	n/a	n/a	DG did not trip or SD	DG did not trip or SD
BO to DG SD (duration)	n/a	DD:HH:MM	n/a	DD:HH:MM
Fires in time	11:25 pm	2023/11/27		
Synch. to Grid (or BC)	3:45 pm	2023/11/28		
Fires in to BC (duration)	00:16:20	DD:HH:MM		DD:HH:MM
Emissions below limit from BC (end date)	not > limit	not > limit		
Emissions below limit from BC (duration)	n/a	DD:HH:MM		DD:HH:MM

Unit No. 3	Event 1			
Breaker Open (BO)	2:45 am	2023/11/06		
Draught Group (DG) Shut Down (SD)	DG did not trip or SD	DG did not trip or SD		
BO to DG SD (duration)	n/a	DD:HH:MM		
Fires in time				
Synch. to Grid (or BC)				
Fires in to BC (duration)		DD:HH:MM		
Emissions below limit from BC (end date)				
Emissions below limit from BC (duration)		DD:HH:MM		

$KUSILE\ POWER\ STATION'S\ MONTHLY\ EMISSIONS\ REPORT\ FOR\ NOVEMBER\ 2023\ REV\ 02-17/4/AEL/MP311/12/01$

Unit No. 4	Eve	nt 1	Event 2		
Breaker Open (BO)	BO previously	BO previously	10:10 am	2023/11/23	
Draught Group (DG) Shut Down (SD)	n/a	n/a	12:35 pm	2023/11/23	
BO to DG SD (duration)	n/a	DD:HH:MM	00:02:25	DD:HH:MM	
Fires in time			1:05 pm	2023/11/23	
Synch. to Grid (or BC)			4:30 pm	2023/11/23	
Fires in to BC (duration)		DD:HH:MM	00:03:25	DD:HH:MM	
Emissions below limit from BC (end date)			not > limit	not > limit	
Emissions below limit from BC (duration)		DD:HH:MM	n/a	DD:HH:MM	

9. Complaints

Date and time complaint was received	Complaint received	Source code name	Root cause analysis	Calculation of impact/emissions associated with incidents and dispersion modelling of pollutants where applicable.	Measures implemented or to be implemented to prevent recurrence	Date by which measures will be implemented
--------------------------------------	-----------------------	------------------------	---------------------------	--	---	--



10. Sec 30 incident or legal contravention register

To be completed in the case of a Sec 30 incident or a legal contravention

Unit no	Incident start date	Incident end date	Incident cause	Remedial actions	Sec 30 notification report sent	Date DFFE Acknowledged	Date DFFE Accepted	Comments/Ref No
Unit 1	05/11/2023, 11/11/2023, 22/11/2023	07/11/2023, 15/11/2024, 25/11/2023	Only indicative values were available resulting in the station unable to activate the high dust emission response procedure, due lack correlated data. The first 1000-1200	alues were ing in the inactivate the on response ack Spot checks are to be done on units during the next CEMS installation while awaiting correlations for implementation of a preliminary curve. This will Not applicable Exceedances not reported as Sec 30 incidents. The exceedances were noted after retrofitting of data and therefore reported as legal contraventions.			Refer to attached investigation report	
Unit 3	02/11/2023, 29/11/2023	25/11/2023, 30/11/2023	operational hours are associated with high emissions. The material fibres for the installed bag set are 100% PPS and did not assist with the reduction of PM that is provided by the PI or P84 fibre. PM concentration is affected by cleaning system parameters and exposure to high DP. Online cell inspection was ongoing based on cell dust flow meters trends. This was effective in reducing dust from damaged bags but ineffective in reducing high dust concentrations associated with bleed through.	values to monitor and action while awaiting test. Cleaning system setting DP used to start the pulse cleaning will be increased to 1.5kPa from 1.3kPa for a new bag set. In addition to this, the maximum pulse cleaning pressure setting will be limited to 500kPa instead of 600kPa to prevent disturbance of the primary ash cake. The specification for the PPS shall be that used at Kusile going forward will include the PI or P84 fibre final layer. Online bag replacements shall continue as required by the system for PM concentration management.				9