

### Generation

Nkangala District Municipality

P O Box 437

Middelburg

1050

Attention:

Mr V Mahlangu

AND

Directorate: Air Quality Management Services

The Chief Director: Mr S S Maluleka

Department of Environmental Services

Private Bag X447 PRETORIA

0001

Tel: (012) 310 3263

Fax: (012) 320 0488

Date: 2025/01/16

Enquiries: Duvha Environmental Managemei

**\*** +27 13 690 0445

县 +27 66 212 2105

Enquiries: Ms Simthandile Nhlapo

**☎** +27 13 690 0445 **८** +27 66 212 2105

Total number of pages: 14

Total number of annexes: 1

## **DUVHA POWER STATION**

Atmospheric Emission License 17/4/AEL/MP312/11/07

GENERAL MANAGER

DATE





## **DUVHA POWER STATION MONTHLY EMISSIONS REPORT**

Atmospheric Emission License 17/4/AEL/MP312/11/07



## 1 RAW MATERIALS AND PRODUCTS

Day Materials and Day doubt	Raw Material Type	Units	Maximum Permitted Consumption Rate	Consumption Rate Dec-2024
Raw Materials and Products	Coal	Tons	1 400 000	732 828.440
	Fuel Oil	Tons	5 000	5475.01
	Product / By- Product Units Name		Maximum Production Capacity Permitted	Indicative Production Rate Dec-2024
Production Rates	Energy	GWh	2 678.400	1 157.470
	A a b	Tono	not appoified	178 956.7
	Ash	Tons	not specified	170 930.7

Note: Maximum energy rate is as per the maximum capacity stated in the AEL: [3 600 MW] x 24 hrs x days in Month/1000 to convert to GWh

## **2 ENERGY SOURCE CHARACTERISTICS**

Coal Characteristic	Units	Stipulate d Range	Monthly Average Content
CV Content	MJ/kg	18-24	22.04
Sulphur Content	%	0.6 TO >1.2	0.64
Ash Content	%	27 TO 30	24.42

# 3 EMISSION LIMITS (mg/Nm³)

Associated Unit/Stack	РМ	SO <sub>2</sub>	NOx
Unit 1	100	3500	1100
Unit 2	100	3500	1100
Unit 3	100	3500	1100
Unit 4	100	3500	1100
Unit 5	100	3500	1100
Unit 6	100	3500	1100

## 4 ABATEMENT TECHNOLOGY (%)

Associated Unit/Stack	Technology Type	Efficiency Dec-2024	Technology Type	SO₃ Utlization Dec-2024
Unit 1	FFP	99.9%	SO₃	n/a
Unit 2	FFP	99.9%	SO <sub>3</sub>	n/a
Unit 3	FFP	Off	SO <sub>3</sub>	n/a
Unit 4	ESP + SO₃	99.7%	SO₃	96.4%
Unit 5	ESP + SO₃	99.8%	SO₃	99.7%
Unit 6	ESP + SO₃	99.8%	SO <sub>3</sub>	99.8%

**Note**: ESP plant does not have bypass mode operation, hence plant 100% Utilised.

## 5 MONITOR RELIABILITY (%)

Associated Unit/Stack	PM	SO <sub>2</sub>	NO	O <sub>2</sub>
Unit 1	100.0	100.0	100.0	100.0
Unit 2	100.0	100.0	100.0	100.0
Unit 3	Off	Off	Off	Off
Unit 4	99.9	42.6	42.6	42.6
Unit 5	100.0	52.8	52.8	56.0
Unit 6	100.0	100.0	100.0	100.0

Note: NOx emissions is measured as NO in PPM. Final NOx value is expressed as total NO2

## **6 EMISSION PERFORMANCE**

Table 6.1: Monthly tonnages for the month of December 2024

Associated Unit/Stack	PM (tons)	SO <sub>2</sub> (tons)	NO <sub>x</sub> (tons)
Unit 1	37.9	6 557	2 188
Unit 2	34.9	2 855	1 473
Unit 3	Off	Off	Off
Unit 4	72.8	1 922	861
Unit 5	59.6	1 287	545
Unit 6	45.1	1 628	993
SUM	250.24	14 249	6 061

Table 6.2: Operating days in compliance to PM AEL Limit - December 2024

Associated Unit/Stack	Normal	Grace	Section 30	Contravention	Total Exceedance	Average PM (mg/Nm³)
Unit 1	30	0	0	0	0	21.0
Unit 2	31	0	0	0	0	21.3
Unit 3	Off	Off	Off	Off	Off	Off
Unit 4	30	1	0	0	1	51.0
Unit 5	25	0	0	0	0	65.9
Unit 6	20	0	0	0	0	43.1
SUM	136	1	0	0	1	

Table 6.3: Operating days in compliance to SO<sub>2</sub> AEL Limit - December 2024

Associated Unit/Stack	Normal	Grace	Section 30	Contravention	Total Exceedance	Average SO <sub>2</sub> (mg/Nm³)
Unit 1	10	0	0	21	21	3 530.9
Unit 2	31	0	0	0	0	1 679.2
Unit 3	Off	Off	Off	Off	Off	Off
Unit 4	31	0	0	0	0	1 296.6
Unit 5	25	0	0	0	0	1 314.0
Unit 6	20	0	0	0	0	1 447.1
SUM	117	0	0	21	21	

Table 6.4: Operating days in compliance to NOx AEL Limit - December 2024

Associated Unit/Stack	Normal	Grace	Section 30	Contravention	Total Exceedance	Average NOx (mg/Nm³)
Unit 1	5	0	0	26	26	1 170.2
Unit 2	31	0	0	0	0	866.4
Unit 3	Off	Off	Off	Off	Off	Off
Unit 4	31	0	0	0	0	580.9
Unit 5	25	0	0	0	0	551.4
Unit 6	20	0	0	0	0	878.9
SUM	112	0	0	26	26	

Note: NO<sub>x</sub> emissions is measured as NO in PPM. Final NO<sub>x</sub>

value is expressed as total NO2

Table 6.5: Legend Description

Condition	Colour	Description			
	Name of the Control o				
Normal		Emissions below Emission Limit Value (ELV)			
Grace		Emissions above the ELV during grace period			
Section 30		Emissions above ELV during a NEMA S30 incident			
Contravention		Emissions above ELV but outside grace or S30 incident conditions			






Figure 2: Duvha Unit 2 PM Emissions - December 2024









Figure 3: Duvha Unit 4 PM Emissions - December 2024



















Figure 8: Duvha Unit 4 SO<sub>2</sub> Emissions - December 2024





Figure 9: Duvha Unit 5 SO<sub>2</sub> Emissions - December 2024






Figure 11: Duvha Unit 1 NOx Emissions - December 2024




Figure 12: Duvha Unit 2 NOx Emissions - December 2024




Figure 13: Duvha Unit 4 NOx Emissions - December 2024




Figure 14: Duvha Unit 5 NOx Emissions - December 2024





Figure 15: Duvha Unit 6 NOx Emissions - December 2024



Tables 7.1: Shut-down and light-up information for the month of December 2024

Unit No.1	Event 1		Eve	ent 2
Breaker Open (BO)			5:00 am	2024/12/04
Draught Group (DG) Shut Down (SD)			DG did not trip or SD	DG did not trip or SD
BO to DG SD (duration)		DD:HH:MM	n/a	DD:HH:MM
Fires in time				
Synch. to Grid (or BC)	11:00 am	2024/12/01		
Fires in to BC (duration)		DD:HH:MM		DD:HH:MM
Emissions below limit from BC (end date)				
Emissions below limit from BC (duration)		DD:HH:MM		DD:HH:MM

Unit No.2	Event 1				
Breaker Open (BO)	11:25 am	2024/12/19			
Draught Group (DG) Shut Down (SD)	DG did not trip or SD	DG did not trip or SD			
BO to DG SD (duration)	n/a	DD:HH:MM			
Fires in time					
Synch. to Grid (or BC)					
Fires in to BC (duration)		DD:HH:MM			
Emissions below limit from BC (end date)					
Emissions below limit from BC (duration)		DD:HH:MM			

Unit No.4	Ev	ent 1
Breaker Open (BO)	9:15 am	2024/12/24
Draught Group (DG) Shut Down (SD)	DG did not trip or SD	DG did not trip or SD
BO to DG SD (duration)	n/a	DD:HH:MM
Fires in time		
Synch. to Grid (or BC)		
Fires in to BC (duration)		DD:HH:MM
Emissions below limit from BC (end date)		
Emissions below limit from BC (duration)		DD:HH:MM

Unit No.5	Event 1		Event 2		Event 3	
Breaker Open (BO)	7:50 am	2024/12/07	6:45 am	2024/12/11	12:30 am	2024/12/25
Draught Group (DG) Shut Down (SD)	10:55 am	2024/12/07	DG did not trip or SD	DG did not trip or SD	3:25 am	2024/12/26
BO to DG SD (duration)	00:03:05	DD:HH:MM	n/a	DD:HH:MM	01:02:55	DD:HH:MM
Fires in time	3:30 pm	2024/12/0 7				
Synch. to Grid (or BC)	10:30 pm	2024/12/0 7				
Fires in to BC (duration)	00:07:00	DD:HH:MM		DD:HH:MM		DD:HH:MM
Emissions below limit from BC (end date)	not > limit	not > limit				
Emissions below limit from BC (duration)	n/a	DD:HH:MM		DD:HH:MM		DD:HH:MM

Unit No.6	Eve	Event 1		nt 2
Breaker Open (BO)	6:50 am	2024/12/14	5:40 pm	2024/12/20
Draught Group (DG) Shut Down (SD)	DG did not trip or SD	DG did not trip or SD	6:35 am	2024/12/23
BO to DG SD (duration)	n/a	DD:HH:MM	02:12:55	DD:HH:MM
Fires in time				
Synch. to Grid (or BC)				
Fires in to BC (duration)		DD:HH:MM		DD:HH:MM
Emissions below limit from BC (end date)				
Emissions below limit from BC (duration)		DD:HH:MM		DD:HH:MM

## 8 COMPLAINTS

There were no complaints for this month.

Source Code / Name	Root Cause Analysis	Calculation of Impacts / emissions associated with the incident	Dispersion modeling of pollutants where applicable	Measures implemented to prevent reoccurrence

### 9 GENERAL

#### Exceedance: Particulate Matter.

#### Unit 4

### 05/12/2024

The process air fan-VSD was being replaced and as a safety precautionary measure to replace the process air fan-VSD, the SO3 plant had to be shut down

Additionally, the reasons for the SOx and NOx gas exceedances for the month of December 2024 are attached in an investigation report as appendix A

The fuel oil usage for the month of December 2024 exceeded the permitted consumption rate due to the following reasons

#### Unit 1

- There was a hot unit light up on the 1<sup>st</sup> and 4<sup>th</sup> of December 2024
- There was a Half-load and 3 mills loading due to unavailability of EFP from the 1<sup>st</sup> to the 6<sup>th</sup> of December 2024 There was also a B EFP Repair in progress which was estimated to be completed on the 3<sup>rd</sup> but ended up being repaired on the 6<sup>th</sup> of December 2024
- There was a Support combustion while soot blowing the boiler
- There was a Mills swap on the unit

### Unit 2

- There was a hot unit light up on the 19th of December 2024
- The unit was continuously supported with B row oil burners due to the ash plant not being available
- There was a support combustion while soot blowing the boiler
- There was a Mills swap on the unit

### Unit 4

- The Unit was on half load with 3 mills loading due to high vacuum and unstable combustion,
- The unit was Continuously supported by B1&B4 oil burner support due to a low load due to the main condenser vacuum deteriorating
- The unit had a support combustion while ashing the boiler (D, B & E row of oil burners)
- The unit had a Support combustion while soot blowing the boiler on low load

### Unit 5

- Mills were not available (there was continuously supporting unstable combustion)
- There was Support combustion while soot blowing the boiler
- There was a Hot unit Return to service on the 7th and 11th
- The unit ran on low load to preserve coal (the coal bunkers were low)

### Unit 6

- The mills were shut down and the unit was left with two mills (A and C mills) that had no coal
- There was Support combustion while soot blowing the boiler
- The B mill was supported with oil burners due to the unstable bottom pyro

Lastly the averages for Oxygen (O2) and Carbon Dioxide (CO2) data from the QAL2 tests reports were used for reporting gaseous emissions for units 2, 4, 5 and 6 due to poor performance of the O2 and CO2 gaseous monitors. The poor performance of the monitors, on multiple units was because of the station's inability to conduct bi-weekly calibrations and preventative maintenance of the O2 analysers for an extended period of time

The lack of preventative maintenance on the O<sub>2</sub> Analysers is because the station historically did not have a long-term maintenance contract for this purpose. When a contract was eventually placed in October 2024, a fault-finding exercise conducted by the Service Provider (SI Analytics Pty Ltd) gave an indication that the lack of maintenance of this plant has resulted in a lot of issues with the equipment

The Station has given the Service Provider time to resolve these issues idetified with the monitors and the monitors are expected to perform at 80% reliability by 31 April 2025. The reasons for the delays are covered in Annexure A.

The rest of the information demonstrating compliance with the emission license conditions is supplied in the annual emission report which will be sent to your office

## 10 S30 Incidents Register

There were no section 30 incidents for this month

Engineering Manager Date

Compiled

by Environmental Officer

Plant Engineering Manager

For Nkangala District Municipality Air Quality Officer

Copies Generation Environmental Management D Herbst
B Mccourt

Generation Compliance Management R Rampiar

Generation Asset Management E Patel

Duvha Power Station Engineering Manager

Operating Manager Maintenance Manager Production Manager

Boiler Engineering Manager

System Engineer

Environmental Manager



# Duvha Power Station Environmental Incident One Pager Report

DUVHA POWER STATION UNIT 1 SOx and NOx EXCEEDANCE (DUVHA POWER STATION ATMOSPHERIC EMISSION LICENCE (AEL) NO. NDM/AEL/MP312/11/07 INCIDENT DATE: DECEMBER 2024.

### BACKGROUND INFORMATION

Duvha Power station has gaseous Continuous Emissions Monitoring System (CEMS) installed at 150-metre level of all flue gas stacks. According to the Duvha Atmospheric Emissions License and Eskom Standard for Emission Monitoring & Reporting 240-56242363, the Gaseous CEMS must be calibrated bi-weekly and must have a minimum availability of 80%.

The Station's Gaseous emissions for SOx and NOx generally performs below the AEL limit of 1100mg/Nm3. However, during the month of December 2024 the Duvha U1 SOx and NOx CEMS recorded readings higher than the maximum allowable limit of 1100mg/Nm3. Figure 1 and 2 below depicts the number of days when the South Stack U1 SOX and NOx Gaseous CEMS exceeded the maximum allowable limit of 1100mg/Nm3. Essentially, from figure 1 and 2 it can be concluded that the exceedances occurred from the 6th till the 31st of December 2024.




Figure 1: Duvha Unit 1 SOx Emissions - October 2024



# CLOSE ENGINEERING CHANGE/EMERGENCY FORM

Template Identifier	240-70976454 (Rev 3)
Document Identifier	<xxx-xxx></xxx-xxx>
Doc Revision	<x.x></x.x>
Next Review Date	May 2028
Gx Engineering	Page 2 of 3
	1

### PUBLIC DISCLOSURE

When downloaded from the EDMS, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.




Figure 2: Duvha Unit 1 NOx Emissions - October 2024

The Unit 1 Gaseous CEMS was last calibrated on the 28th of November 2024, which means that the Gaseous CEMS have not been calibrated bi-weekly as per the requirement from Eskom Standard for Emission Monitoring & Reporting 240-56242363 due to the unavailability of the stack lifts. It can be concluded that the data integrity of the Duvha Gaseous CEMS is compromised and therefore the readings are not accurate. The smoke stack lifts are out of service due to the following reasons:

- As per clause 6(2) of the Occupational Health and Safety act 85 OF 1993; Lift, Escalator and passenger Conveyor regulations, 2010; Published under Government Notice R828 in Government Gazette 33561 of 17 September 2010:
- "If an inspection or test carried out by an inspection service provider on a lift, escalator or passenger conveyor shows that any defect or weakness exists whereby persons are endangered, the inspection service provider shall report such defect or weakness forthwith to the user, the competent lift service provider and the provincial director, and no person shall be conveyed or allowed to be conveyed in or on such lift, escalator or passenger conveyor until such defect has been rectified to the satisfaction of the inspection service provider."
- 2. The lift inspection service provider deemed the lift safety device unsafe and required that it be calibrated or modernized such that it is marked at what speed it is tripping. This defect needs to be rectified.

### PUBLIC DISCLOSURE

When downloaded from the EDMS, this document is uncontrolled and the responsibility rests with the user to ensure it is in line with the authorised version on the system.



# **CLOSE ENGINEERING** CHANGE/EMERGENCY **FORM**

Template Identifier	240-70976454 (Rev 3)
Document Identifier	<xxx-xxx></xxx-xxx>
Doc Revision	<x.x></x.x>
Next Review Date	May 2028
Gx Engineering	Page 3 of 3

To rectify this defect the Electrical Maintenance Department has conducted a plan to replace the smoke stack lifts Overspeed Governor. This process is at procurement stage and the expected completion date is 22 April 2025.

Compiled by:

Lethu Ndwandwe

**C&I System Engineer** 

Approved by: Lungani Buthelezi

**C&I Maintenance Manager**