NAME	1 TRANSFERS ASH CONV 1 (AC1 – AC2	2 DYPSUM TRANSFER CONV 4 (CY2A–CY2B)	3 GYPSUM TRANSFER CONV 3 (CY1A–CY1B)	4 EMERGENCY ASH RE-CONVEYOR – ESC	5 EMERGENCY STACKING CONVEYOR – ESC	6 TRANSFERS ASH CONV 5 (AC3 – AC4)	7 STRAIGHT ASH STACKER CONV – CAC2	8 RADIAL STACKER CONVEYOR – RSC
OPERATING CAPACITY	2340 tph	140 tph	410 tph	360 tph	360 tph	1440 tph	1440 tph	1440 tph
DESIGN CAPACITY	2340 tph	140 tph	410 tph	360 tph	2340 tph	1440 tph	1440 tph	1440 tph
BELT WIDTH	1350 B/W	500 B/W	500 B/W	1350 B/W	1350 B/W	1350 B/W	1350 B/W	1350 B/W
BELT SPEED	4 m/s	2 m/s	2 m/s	3.7 m/s	4.2 m/s	4.2 m/s	3.0 m/s	3 m/s
% LOAD	91 %	10 %	10 %	25 %	91 %	91 %	15 %	91 %
LENGTH	1085 m	230 m	264.2 m	278 m	295 m	824 m	74 m	36.5 m
LIFT	10 m	0.1 m	19.3 m	0 m	8.8 m	3.1 m	11.7 m	8.8 m
MATERIAL SIZE	–0.5 mm	1mm	1mm	–0.1mm	–0.5mm	–0.5mm	–0.5mm	–0.5mm
INSTALLED POWER	280 kW	30 kW	45 kW	55 kW	280 kW	355 kW	30 kW	90 kW
RSS NUMBER	1 DETH201 AF001 6 DETH10 AF001	3 DHPT01 AF001 3 DHPT10 AF001	5 DHPT11 AF001 5 DHPT21 AF001	0 DETH31 AF001	5 DETH30 AF001	5 DETH21 AF001 3 DETH10 AF001 4 DETH20 AF001 2 DETH30 AF001 6 DETH40 AF001	1 DETH01 AF001 5 DETH10 AF001 4 DETH20 AF001 2 DETH30 AF001 6 DETH40 AF001	5 DETH

WIL53615 09-JUL-2012 14:06:13

P146838.61.0403.05-04001 0001 St:EN 18-MAY-12 MS-05974